Technical Specifications

| Model u401cl | DY020A |
|-----------------------------|---|
| Processor & Speed | 2.6 GHz/400 Intel® Celeron™ Processor – PGA478 |
| Chipset | Intel® 845GV |
| Motherboard | Gamila-GL6E (MS-6577) |
| RAM | 256/2700 MB 333DDR SDRAM (runs@266MHz) |
| Maximum | 2 GB (2x1024MB DDR SDRAM) |
| Sockets | Two 184-pin DDR DIMMs |
| Size | 128, 256, 512 AND 1024 MB DDR DIMMs |
| Free DIMM Sockets | One |
| Pairs Required | No |
| Type Supported | JEDEC unbuffered DDR SDRAM DIMM specification |
| Cache | 8KB Data Cache + Trace Cache L1, 128 KB L2 Integrated on Processor module |
| Hard Drive | 40 GB (5400RPM) |
| Optical Drive | DVD-ROM Drive: DVD (16x max.) / CD-ROM (48x max.) |
| Access Speed | DVD =115ms / CD-ROM =95ms |
| Transfer Rate | DVD = 21.6/sec. / CD-ROM = 7.2MB/sec. |
| Diskette Drive | None |
| 7 in 1 Card Reader | Compact Flash I/II; Memory Stick/Pro; MMC/SD; Smart Media |
| Fax/Data Modem | V.92 56Kbps |
| Fax Speed | Up to 14.4Kbps |
| Data Compression | V.42 bis |
| Error Correction | V .42 |
| EIA Fax Commands | Class 1 |
| Video Graphics | Intel® Extreme Graphics |
| Controller | Integrated w/845G Chipset |
| Video Memory | Dynamic up to 64MB UMA |
| Network Card | 10/100 BaseT, Integrated |
| 1394 Card | IEEE-1394, Integrated |
| Sound | AC'97, 6 Channel, Integrated on MB |
| Controller | Realtek ALC650/658 |
| Chassis | Panther, 250HV + PFC PSU |
| USB Interface Specification | USB 2.0 |
| External Ports | 5= USB, 1= serial, 1= parallel, 2=1394 |
| Front I/O Connector | 1 = USB, 1 = 1394; 7 in 1 Card Reader; 1 = Microphone; 1 = Line-In; 1 = Headphone |
| Expansion Slots (Total) | 3= PCI |
| Expansion Slots (FREE) | 2= PCI |
| Drive Bays (Total) | Two 5.25" external, One 3.5" external, Two 3.5" internal |
| Drive Bays (FREE) | One 5.25" external, One 3.5" external, One 3.5" internal |
| Keyboard/Mouse | One-touch Enhanced Keyboard, PS/2 Optical scrolling mouse |